

# Product Data Sheet

## Cromadex Liquid Coatings Cromadex Anti-Silicone Additive

### Product Description

Cromadex Anti-Silicone additive is designed to be added to selected Cromadex topcoats to aid paint application where silicone contamination may be present, helping to reduce coating rejection.

The product can be used in Cromadex 222, 233, 400, 600 and 800 topcoats.

### Products and Ancillaries

KS1A14 Anti-Silicone Additive

### Preparation

Whilst this product is likely to be used in environments subject to silicone contamination, full preparation guidelines should be followed from the relevant product data sheet

### Procedure

To be added to the following Cromadex topcoats in the following quantities:

- 222 = 10ml per litre of base pack
- 233 = 10ml per litre of base pack
- 400 = 20ml per litre of base pack
- 600 = 20ml per litre of base pack
- 800 = 10ml per litre of base pack

Anti-Silicone Additive should be added prior to thinning and catalysing (i.e. to the "base pack"). It should only be added immediately prior to application. Paint with the additive should not be stored.

### Drying Times

Drying times of the relevant product will not be affected. Please see relevant product data sheet.

### Storage and Handling

<b>Storage</b>	Storage should be in accordance with the instructions in Section 7 of the relevant material safety data sheet
<b>Shelf Life</b>	24 months in an unopened, original container from date of manufacture
<b>Pack Size</b>	250 ml plastic bottle with 10 ml dispenser

### Physical Properties

<b>Flash Point</b>	23°C
<b>Pot Life</b>	Pot Life of two pack products will be unaffected when using Cromadex Anti-Silicone Additive. Please consult relevant product data sheet
<b>Colour</b>	Clear
<b>VOC</b>	828 g/l
<b>Specific Gravity</b>	0.97

### Safety Precautions and Disclaimer

**Before using this product please refer to the Cromadex Material Safety Data Sheet.**

The information contained in this data sheet is not intended to be exhaustive, and any person using the product without first obtaining written confirmation from us as to the suitability of the product for the intended purposes, does so at their own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability whatsoever arising from the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

It is the user's responsibility to check that this data sheet is current prior to using the product.